

CENTURY HARDWARE & BLUE BELL LUMBER Est 1936

Your Complete Source for Building Construction & Maintenance Supplies



EVO LUX®
LUXURY EVOLVING

**Fume SPC- Luxury
Vinyl Plank Flooring**

Fume- Luxury Vinyl Plank

SPC Rigid Core Click Floating- 12 Mil- 4.5mm - 7"x48" Plank

4.5 mm



IXPE Pad Attached

7"x48" 12 mil - Wood Embossed
18x122 cm

28.68 Sq Ft Per Case

✓ Green Check Mark Signifies Stock Color



Cotton

7"x48"

MODEL #- EVFUME1L4

Lead Time- 3-5 Days



Silk ✓

7"x48"

MODEL #- EVFUMELO3

In Stock- Next Day Delivery

Century Item # - LVP12-GR



Honey

7"x48"

MODEL #- EVFUMELO4

Lead Time- 3-5 Days



Maple

7"x48"

MODEL #- EVFUMELO7

Lead Time- 3-5 Days



Canela

7"x48"

MODEL #- EVFUME3L5

Lead Time- 3-5 Days



Tabacco ✓

7"x48"

MODEL #- EVFUME623

In Stock- Next Day Delivery

Century Item #- LVP12-TB

Fume SPC

SPC Rigid Core Click Floating- 12 Mil- 4.5mm

Size: 7" x 48"

Sq Ft Per Carton: 28.68

PC per Carton: 12

Cartons per Pallet: 60

Fume offers a bold and dramatic wood-inspired look, its deep tones providing a strong and sophisticated foundation for a variety of decor styles.

SPC:

Also known as interlocking LVP, features a locking mechanism that allows the tiles or planks to be clicked together during installation.

No adhesive is required for installation, as the tiles or planks are locked together.

SPC Rigid Core Click Floating - 12mil - Wood Embossed





Fume Cotton 7"x48"



Fume Canela 7"x48"



Fume Tabacco 7"x48"

Fume

SPC Rigid Core Click Floating

Technical Specifications

	Standard	Result
Thickness		4.5mm
Size		7"x48"
Material		SPC
Wear Layer		12 mil
Surface Treatment		Nano Silver Coating
Surface Texture		Wood Emboss
Padding		1mm IXPE
Warranty	Commercial / Residential	10 year Commercial / Limited Lifetime Residential
Installation		Unilin Click
Beveled Edge		No
Smoke Density	ASTM E662-06	Pass <450
Slip resistance	ASTM C1028	Pass
Staining resistance	ASTM F925	Pass
Light Resistance	ASTM F1515	Pass
Abrasion resistance	ASTM D4060	Pass
Dimensional stability	ASTM F2199	Pass
Acoustic impact noise reduction IIC	ASTM E492-09	IIC = 62 dB concrete slab 6" drop ceiling
Calculated Sound Transmission STC	ASTM E413-16	STC = 68 db
Static load	ASTM F970-17	Pass
Indentation	ASTM F1914	Pass
Phthalate free		Yes



Packaging Information

Size	SF per carton	PC per carton	BX per pallet
7"x48"	28.68	12	60